Regeneratable, low flow resistance, adsorber for vent gases - comprises fluidised bed and fixed bed sections

Patent number:

DE4020246

Publication date:

1992-01-02

Inventor:

SIEBER HELMUT (DE)

Applicant:

BOEWE PASSAT REINIGUNG (DE)

Classification:

- international:

B01D53/12; B01D53/06; (IPC1-7): B01D53/02;

B01J20/20; C01B31/08

- european:

B01D53/12

Application number: DE19904020246 19900626 Priority number(s): DE19904020246 19900626

Report a data error here

Abstract of DE4020246

Vapours are adsorbed from an air or carrier gas stream by passing the flow through a container of adsorbent materials comprising a first section of loose granules and a second section of fixed adsorbent. The container dimensions relative to the gas flow are such that the loose granules form a fluidised bed; entrainment loss is prevented by the porous fixed adsorbent layer which forms a significant proportion of the pressure loss but is able to reduce residual vapour in the outlet gas stream to a lower level than the fluid bed alone. USE/ADVANTAGE - Solvent recovery from gas streams, e.g. dry cleaning machine vents. Combines the low flow resistance of the fluidised bed with the higher overall recovery of a fixed bed absorber.

Data supplied from the esp@cenet database - Worldwide